

Manager IQ Easy
1030000000 - 24V DC powered
1030000010 - 100-240V AC powered

Sub-D connector
male 25 pole
3900236025

Power cord IEC-C13
2 m, with lock
9146340700

24V power connector
for Ø4 - 6,5 mm cables
9370000205

Extension IQ Easy
1030000100 - 24V DC powered
10300000110 - 100-240V AC powered

Connector IQ M12 male straight
5 pole (screw connections)
7519020352 - Ø4-6 mm cables
7519020353 - Ø6-8 mm cables

Status Module
4530000300

Cord IQ interconnection M8
female-male straight 3 pole
7519020291 - 5m
7519020292 - 10m
7519020294 - 25m

Cord device M12 female angled 5 pole

7519020375 - 5 m, unshielded
7519020376 - 10 m, unshielded

Cord device M12 female straight 5 pole

7519020365 - 5 m, unshielded
7519020366 - 10 m, unshielded

Connector device M12 female angled
5 pole (screw connections)

7519020355 - Ø4-6 mm cables
7519020356 - Ø6-8 mm cables

Connector device M12 female straight
5 pole (screw connections)

7519020350 - Ø4-6 mm cables
7519020351 - Ø6-8 mm cables

Cord device M12 fem.-male straight 5 pole

7519020390 - 2m, unshielded
7519020391 - 5m, unshielded
7519020392 - 10m, unshielded
7519020393 - 20m, unshielded
7519020394 - 25m, unshielded

Protective hose ATEX

9380531320 per m

Hose clip ATEX

9250101013 needed 4 pieces/m hose

Fitting ATEX

9370521017

ATEX ZONE

NON-ATEX ZONE

Ex Certified Product
No modifications permitted without the approval of the "authorised person"

Remark:

- The Status Module Performax (IQ) Easy EX has a connection for one bar

SIMCO ION
An ITW Company

www.simco-ion.nl Tel: +31 (0)573 288333

Name: Performax IQ Easy EX (Speed) system overview

Drawn: RJ

Part no.: —

CAD generated
NOT updated

Dimensions
in mm

Date: 7-2-2017

A3

M: 1:1

ECN-

Check: -

Dwg. no.: 15350100/A